



IGLOO S2700 AST

Advanced Spreading Technology



- the safe way

The IGLOO S2700

- easy to operate and service-friendly

The IGLOO S2700 series is ideal for spreading salt, sand and other materials generally used for the treatment of icy roads.

The IGLOO S2700 is width/amount-compensated and road-independent (synchronous), which means that the set spreading amount per m² remains constant regardless of changes in spreading width or vehicle speed.

The S2700 is ideal for fitting smaller trucks, trailers and carrying vehicles. You can get the S2700 with a variety of hopper sizes.

The S2700 is also available as an extended model.



”

- Modular construction
- Manageable engine compartment
- Variable pre-wetting at 7-100%
- Optimal centre of gravity positioning
- Easy operation and servicing
- GPS & Temperature controlled spreading



Manageable and service-friendly engine compartment.



Can be powered by hub drive from the vehicle.



Long rear end for optimal centre of gravity positioning.
Stainless spreading disc and funnel.

OPTIONS



- Long rear end - model S & M
- Pre-Wetting unit 30%
- Variable pre-wetting 5-100%
- Operation: Hydraulics from vehicle, rotopower, petrol engine, or wheel pump - if the spreader is on trailer
- Foldable tarpaulin (full opening)
- Electrically controlled spreading symmetry
- Undloading system on adjustable legs
- Stainless steel version
- Stress relief plate over conveyor belt*
- Centre of gravity stabilisation*
- Remote control - EpoMini X1
- Remote control - EpoMaster X1
- Remote control - EpoMaster X2
- EpoSat - GPS-controlled spreading
- Data collection

(*Does not apply to the XS model).



The spreader can also be delivered for installation on tractor trailer.



The belt spreader is operated as standard using an EpoMini X1 remote control.



Optional: EpoMaster X2, which provides option for GPS-controlled spreading and navigation.

Spreader series	XS	S	M	L
Hopper capacity [L]	600 - 800	800 - 1100	1100 - 1400	1400 - 2000
Tank capacity, liquid [L]	344	440 - 536	612 - 688	784 - 880
Spreading width [m]	2 - 6			
Application, dry matter [g/m ²]	5 - 40			
Pre-wetting percentage [%]	7 - 100			
Spreading speed [km/h]	0 - 40			
Filling speed, max. [L/min]	400			
Total width [mm]	1360			
Total height [mm]	890 - 980	890 - 980	890 - 980	890 - 1160
Total length [mm]	TBD	1825/2325	2345/2845	2785/3285
Truck floor height, min.-max. [mm]	720 - 1433			
Remote control	EpoMaster X2 / EpoMaster X1 / EpoMini X1			
Options (dependent on remote control)	EpoSat / EpoTherm / EpoData			

Epoke Group

We produced our first sand and salt spreader in 1955, and since then we have solely focused on the development, production and sale of machines and equipment for the treatment of icy roads. Today, we are a global leader. In Denmark, sales are carried out by our own sales staff, while abroad our subsidiaries and 31 dealers manage sales.

Learn more at www.epoke.dk

Epoke A/S
 Vejervej 50
 DK-6600 Vejen,
 Denmark
www.epoke.dkk

